

STANDARD SPECIFICATIONS

1977

BASIC CONSTRUCTION:

- Patented Air-Flow contoured shape
- Exclusive Aero-Stress high-strength steel undercarriage
- Extruded aluminum bumper
- Dura-Torque torsion bar axles
- Shock absorbers on all wheels
- Tandem wheels on all models except 21'
- Excella-Vac disc brakes
- Automatic break-away control
- 15" Truck-type extra strength wheels with 7:00 x 15 nylon tubeless tires (D-rated on single axle models; C-rated on double axle models).
- Hand riveted monocoque shell of heat treated structural alloy aluminum
- Exterior protective acrylic coating
- Ribs of stretch-formed structural alloy aluminum
- Interior walls of wear-resistant vinyl laminated to aluminum
- One-piece stretch-formed extruded aluminum window frames riveted to body
- Exclusive contoured Jet-Seal awning-type Herculite safety glass windows
- Super strength front window (Herculite safety glass)
- Corrosion-proof screens in all windows
- Exclusive touch-control fold-away aluminum entrance step
- Univolt convenience light in rear service area and side trunk area
- Awning rail
- Double-walled fiberglass insulated wheel wells
- 2¼ inch aircraft type fiberglass insulation
- Adjustable, no-draft aluminum roof vents

ELECTRICAL EQUIPMENT:

- A.N.S.I., D.O.H., C.S.A. and N.E.C. Code-approved wiring system
- Detachable single-plug weatherproofed car-trailer connector (includes 12 volt charge line)
- Two-bulb, corrosion-proof 180° visibility exterior clearance and running lights (installed in conformance with Federal Motor Vehicle Safety Standard 108)
- Back-up lights
- Built-in 110 volt service line (25 feet)
- Extra-capacity 105 ampere hour 12 volt battery in built-in, sealed and vented battery compartment

- Exclusive exterior electrical duplex outlet
- Three-position Univolt ceiling lights combined with ceiling vents
- Exclusive, one knob variable position ceiling vents
- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery
- Overload safety fuse cartridges in Univolt wiring system
- Circuit breakers on 110 volt wiring system

PLUMBING:

- A.N.S.I., D.O.H. and C.S.A. Code-approved plumbing system
- High volume water pressure regulator in water inlet line
- Lockable, flush water fill
- Univolt marine pump (capacity 3 gallons per minute)
- 45 Gallon polyethylene water tank
- Swing faucet at double galley sinks
- Stainless steel galley sinks
- Exclusive all thermo-formed bathroom with bathtub in 25-foot Caravanner, 27, 29, and 31-foot models. Stall shower in 27, 29 and 31-foot center bath models. Stall shower in 21, 23 and 25-foot models.
- Built-in medicine cabinet and mirror
- Panoramic roof lockers with roll-away doors in full bath models
- Large pullman lavatory
- Clothes hamper and bag (Full bath only)
- Make-up lighting
- Water-saver "telephone" shower
- Mechanical seal, flush toilet
- Polyethylene holding tanks of approximately one week capacity
- Drainage drop-out cover cap
- Drainage drop-out elbow for connecting sewer hose
- Built-in sewer hose carrier

GAS EQUIPMENT:

- A.N.S.I., D.O.H. and C.S.A. Code-approved gas system
- All gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers
- Double 7 gallon gas bottles
- Sealed, outside vented, forced air gas space heater (input ratings: 21' Globetrotter, 16,500 B.T.U.; 23' Safari and 25' Tradewind, 22,000 B.T.U.; 27' Overlander, 29' Ambassador and 31' Sovereign of the Road, 30,000 B.T.U.)

- Automatic heater thermostat
- Automatic igniter for space heater
- Univolt blower and circulating ducts
- Gas/electric combination refrigerator: 4.5 cubic foot in 21' Globetrotter; 6 cubic foot in 23' Safari, 25' Tradewind. All other models, 10 cubic feet.
- Gas range with oven and broiler
- Range vent hood
- Adjustable exhaust vent. Includes motor on International.
- 'Super 6' water heater on all models
- Built-in igniter on gas water heater

FURNISHINGS:

- Exclusive all new Perma-Tech II furniture construction featuring heat-treated, color-anodized aluminum framework with textured high-pressure laminate panels
- Lightweight warp-free honeycomb doors
- Roll-away cabinet and roof locker doors
- Posi-Lock latches on all cabinet doors
- Drawers of lightweight high-impact styrene
- Silverware drawer
- Credenza fold-away table in all models with front travel lounge
- Six inch foam fixed mattresses in bedroom with zippered covers
- Carpeting in all areas, all models. Nylon.
- All upholstery treated with SCOTCHGARD repeller to resist soiling
- All draperies fade resistant and pre-shrunk
- All draperies lined
- Decorator-styled, washable vinyl window shades at galley and bathroom windows
- Full length mirror
- Slide-away bathroom door
- Bedroom vinyl folding door in 23' models and longer

DIMENSIONS:

- Outside floor width . . . 7'8"
- Outside height from ground . . . 8'10"
- Inside height (floor to ceiling) . . . 6'7"
- Ground clearance . . . 16" to underbelly, 12.24" to axle tube
- Recommended hitch ball height . . . 19½"

All specifications subject to change without notice