

Specifications.

ISHINGS

om folding door. In all models except
Safari
g chair storage area. In all models
of the 23' Safari and the 25' Tradewind
ve "feather touch" one-piece 5th
e lounge
ed credenza fold-away table in side-
a models
ch foam fixed mattresses in bedroom
plush carpeting
holstery treated with SCOTCHGARD
ent to resist soiling
ngth mirror
/ flip-up shelf (except 23' side lounge)
away bathroom door
olor schemes
peries fade-resistant
peries lined
ator-style, washable vinyl window
s at galley and bathroom windows
ve touch-control, fold-away
um entrance step

AGE

eight, warp-free, honeycomb core
our roof locker doors
ok latches on all cabinet doors
rainers of lightweight high-impact
e
eight injection molded galley and
drawers
rare drawer
medicine cabinet and mirror
amic roof lockers with mirror doors in
th models

- High cube galley storage
- Tambour spice rack

DIMENSIONS

- Outside floor width ... 7' 8"
- Outside height from ground ... 8' 10"
- Inside height (floor to ceiling) ... 6' 7"
- Ground clearance ... 16" to underbelly, 12.24" to axle tube
- Recommended hitch ball height ... 19-1/2"

CONSTRUCTION FEATURES

- Patented aerodynamic shape
- Exclusive high-strength steel undercarriage
- Extruded aluminum bumper
- Dura-Torque axles
- Shock absorbers on all wheels
- Tandem wheels on all models
- Automatic breakaway control
- 15" Truck-type extra strength wheels with 7:00 x 15 nylon tubeless tires; C rated
- Hand riveted semi-monocoque shell of heat-treated, structural alloy aluminum
- Exterior protective acrylic coating
- Ribs of stretch-formed structural alloy aluminum
- Interior walls of wear-resistant, vinyl-covered aluminum
- Awning rail
- Double-walled fiber glass insulated wheel wells
- 2-1/4 inch fiber glass insulation

WINDOWS AND VENTS

- New oversize picture window in lounge
- One-piece stretch-formed, extruded aluminum window frames
- Exclusive contoured awning-type Hercutite safety-glass windows

- Corrosion-proof screens in all windows
- Adjustable aluminum roof vents
- Range vent hood with adjustable exhaust vent

PLUMBING AND FIXTURES

- Thermo-formed bathroom with tub. In 28' Ambassador and 31' Sovereign only
- Molded shower stall. In 23' Safari, 25' Tradewind, 31' Center Bath
- High volume water pressure regulator in water inlet line
- Lockable, flush water fill
- Univolt demand pump (capacity 3 gallons per minute)
- Drainage drop-out cover cap
- Drainage drop-out elbow for connecting sewer hose
- Built-in sewer hose carrier
- Mechanical seal, flush toilet
- Swing faucet at double galley sinks
- Stainless steel galley sinks
- Large pullman lavatory
- Water-saver "telephone" shower head
- A.N.S.I., D.O.H. (C.S.A. Optional) Recreation Vehicle Code approved plumbing system

ELECTRICAL AND LIGHTING EQUIPMENT

- A.N.S.I., D.O.H. (C.S.A. Optional) Recreation Vehicle Code approved electrical system
- N.E.C. Code-approved wiring system
- Detachable single-plug weather-proofed car-trailer connector (includes 12 volt charge line)
- One-bulb, corrosion-proof 180° visibility exterior clearance and running lights (installed

- Back-up lights
- Built-in 120-volt service line
- Extra-capacity 105-ampere hour, 12-volt battery in built-in, sealed and vented battery compartment
- 120-volt exterior patio outlet
- Exclusive exterior electrical duplex outlet
- Three-position Univolt ceiling lights combined with ceiling vents
- Exclusive one-knob variable position ceiling vents
- Exclusive ferro-resonant Univolt to convert 120-volt city power to 12-volt direct current power and automatically charge battery
- Overload safety fuse coded panel in Univolt wiring system
- Circuit breakers on 120-volt wiring system
- Interior light switch at door
- Switch center in bathroom
- Univolt convenience light in rear service area and side trunk area
- Make-up lighting
- Univolt blower for heat circulating ducts

GAS EQUIPMENT

- A.N.S.I., D.O.H. (C.S.A. Optional) Recreation Vehicle Code Approved gas system
- Gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers
- Gas space heater: sealed, thermostat-controlled, automatic igniter, outside vented, forced air, input ratings: 23' Safari and 25' Tradewind, 22,000 BTU; 28' Ambassador and 31' Sovereign, 30,000 BTU
- Gas/Electric combination refrigerator: 6 cu. ft. in 23' Safari and 25' Tradewind. All other models, 10 cu. ft.