

GENERAL

Actual length	31'	31'	34'10"	34'10"
Width exterior	8'5.5"	8'5.5"	8'5.5"	8'5.5"
Width interior	8'1"	8'1"	8'1"	8'1"
Height exterior w/air cond.	9'7.5"	9'7.5"	9'7.5"	9'7.5"
Height interior w/air cond.	6'3.5"	6'3.5"	6'3.5"	6'3.5"
Hitch ball height	18.75"	18.75"	18.75"	19.75"
Safety chain hook – 11700 lb rating (meets CSA)	STD	STD	STD	STD
UBW (unit base weight) w/o options or fluids	7110	6990	7990	8300
+ NCC (Net Carrying Capacity) w/o options / personal cargo / fluids (lbs)	2890	3010	3510	3200
= GVWR (Gross Vehicle Weight Rating) (lbs)	10000	10000	11500	11500
Hitch weight, w/o options or variable wt.	890	760	820	1250
30 lb. aluminum LPG bottles(2) w/sight	STD	STD	STD	STD
Water tank w/drain valve, 54 gallon	STD	STD	STD	STD
Black water tank w/tank flush	39	39	39	39
Sewer hose storage	STD	STD	STD	STD
Gray water tank	37	37	37	37
6 gallon gas / electric dsi water heater	STD	STD	STD	STD
Aluminum step w/extension	STD	STD	STD	STD
Electric drum brakes (12")	STD	STD	STD	STD
Slide-out extension: Dinette – interior size 22"d x 76.5"l x 64"h, electric operation, slide-out cover, built-in electrically operated travel locks	—	—	—	STD

SAFETY AND COMFORT

Spare tire & wheel	OPT	OPT	OPT	OPT
Spare tire bracket	STD	STD	STD	STD
Electric hitch jack	STD	STD	STD	STD
Stabilizer jack w/pads (manual)	STD	STD	STD	STD
Stainless steel a-frame protectors	STD	STD	STD	STD
LPG bottle cover	STD	STD	STD	STD
Underbelly – enclosed & insulated	STD	STD	STD	STD
Wrap protectors – stainless steel	STD	STD	STD	STD
Solar stone guard (3-pc)	STD	STD	STD	STD
Level	STD	STD	STD	STD
Keyed deadbolt – manual – entry door	STD	STD	STD	STD
LPG detector / smoke detector / Carbon Monoxide detector	STD	STD	STD	STD
CCC comfort control center	STD	STD	STD	STD
Probeless tank monitoring system	STD	STD	STD	STD

EXTERIOR

Bright aluminum finish (roof finish – white)	STD	STD	STD	STD
Classic blue graphics w/chrome trim inserts	STD	STD	STD	STD
Classic medallion – blue 10" (3)	STD	STD	STD	STD
Molded rear bumper and bumper farrings inc. slide out storage compartment	STD	STD	STD	STD
Wrap protectors – stainless steel	STD	STD	STD	STD
Solar stone guard (3-pc)	STD	STD	STD	STD
Underbelly – enclosed & insulated	STD	STD	STD	STD

INTERIOR

Vista view window 18"	1	2	0	0
Vista view window 30"	2	2	3	1
Screen door guard	STD	STD	STD	STD
Keyed deadbolt – manual – entry door	STD	STD	STD	STD
Stack window S.P. Fwd. Of door (30") 31% light transmission	—	OPT	OPT	OPT
Stack window S.P. Fwd. Of door (18") 31% light transmission	STD	STD	—	—

APPLIANCES

13,500 A/C, w/heater pump & electronic controls	STD	STD	STD	STD
Furnace – 34,000 btu w/electronic ignition	STD	STD	STD	STD
3 burner range w/oven-silver door & top & reg. MWave	STD	STD	OPT	STD
Range hood w/vent – silver	STD	STD	STD	STD
Roof vent (bedroom) exhaust only – delete w/optional bedroom A/C	STD	STD	STD	STD
8.0 cubic ft. 2-way auto refrigerator w/brushed stainless steel door	STD	STD	STD	STD
10.0 cubic ft. 2-way auto refrigerator nd w/brushed stainless steel door	OPT	OPT	OPT	OPT

ENTERTAINMENT & SOUND SYSTEM

AM / FM / CD, Radio antenna, Speakers, mtd & wired (4), Control: 18FM / 12AM presets, 40w x 4 high power output, full detachable face, optional wired remote control	STD	STD	STD	STD
Premium audio upgrade package: 10 disc CD changer, 100 watt active subwoofer, exterior speaker jack, AB switch	OPT	OPT	OPT	OPT
Premium audio/video upgrade package: AM / FM / CD / DVD / CD controller receiver, 6.5", 2-way speakers (2pr), 100 watt active subwoofer, 12 disc CD changer, flat screen TV 15" LCD, articulating wall bracket, exterior speaker jack, AB switch	OPT	OPT	OPT	OPT
TV Ready: includes TV antenna, 2 TV jacks w/12 volt outlet	STD	STD	STD	STD
Cable TV & telephone package includes: cable outlets (2), telephone outlets (2)	STD	STD	STD	STD
Pre-wire for portable satellite dish	STD	STD	STD	STD
Satellite radio option (w/audio upgrade)	OPT	OPT	OPT	OPT
Satellite radio option (w/entertainment upgrade)	OPT	OPT	OPT	OPT

ELECTRICAL

Phone jack – bedroom / living room	STD	STD	STD	STD
7-way trailer plug	STD	STD	STD	STD
55 amp converter	STD	STD	STD	STD
12 volt circuit breakers	STD	STD	STD	STD
12 volt fluorescent recessed ceiling lighting	STD	STD	STD	STD