













16RB









SPECIFICATIONS

MODEL	T12RB	T14BB	T14RBS	T15RL	T16BB	T16RB	T18RBS	T20BBS	T20RLS
EXT LENGTH	15'11"	17'8"	18'6"	20'5"	20'10"	20'10"	22'5"	24'6"	24'6"
EXT WIDTH	84"	84"	84"	84"	84"	84"	84"	84"	84"
INT HEIGHT	78"	78"	78"	78"	78"	78"	78"	78"	78"
GVWR	3,700 lbs	3,850 lbs	5,500 lbs	5,500 lbs	5,500 lbs				
AXLE WEIGHT	1,535 lbs	1,915 lbs	1,975 lbs	2,035 lbs	1,915 lbs	2,120 lbs	2,640 lbs	2,905 lbs	2,905 lbs
HITCH WEIGHT	150 lbs	300 lbs	430 lbs	360 lbs	270 lbs	320 lbs	375 lbs	410 lbs	410 lbs
UVW	1,705 lbs	2,235 lbs	2,425 lbs	2,415 lbs	2,205 lbs	2,460 lbs	3,035 lbs	3,335 lbs	3,335 lbs
PAYLOAD	1,995 lbs	1,615 lbs	1,425 lbs	1,435 lbs	1,645 lbs	1,390 lbs	2,465 lbs	2,165 lbs	2,165 lbs
FRESH WATER	32 gal								
GRAY WATER	15 gal	24 gal	24 gal	24 gal					
BLACK WATER	10 gal	10 gal	10 gal	10 ga	10 gal	10 gal	24 gal	24 gal	24 gal

FEATURES

- 3,500 lb Rated Axle(s)
- 6 gallon gas Water Heater
- Coach Net Road Side Assistance
- Custom Fit LCI Chassis
- Furnace
- Hi Output Cooktop
- Insulated Ceiling, Floor & Walls
- Pillow Top Mattress
- Porcelain Toilet
- Refrigerator
- Seamless One Piece Rubber Roof
- Solid Wood Cabinetry
- TV Antenna Ready
- Upgraded Seat Cushions
- Upgraded Window Treatments
- Upgraded Floor Covering

OPTIONS

- A/C 13.5 BTU
- Aluminum Wheels
- Awning
- Awning Power (18rbs, 20rls, 20bbs)
- Bath Skylight
- Chrome Wheels (4)
- Front Diamond Plate
- Front Stabilizer Jacks
- Front Window w/Rockguard
- Fuel Station 20 Gallons (EX Units)
- Heated Tanks / Valves
- Microwave Over
- Spare Tire & Carrier
- Stab Jacks (4)

All information included in this brochure is the latest at the time of publication. Pacific Coachworks reserves the right to make changes and to discontinue at any time, without notice, prices, colors, materials, equipment, accessories, specifications, models, and packages, without incurring any obligations to make the same or similar changes to trailers. All vehicles built by Pacific Coachworks, Inc. include a one year factory warranty. Roadside Assistance via Coach-Net is also included.

